

Printing date 22.05.2018 Version number 17 Revision: 13.03.2018

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: Osmo Decking Oil

Article number: 004, 006, 007, 009, 010, 013, 014, 016, 019, 021

1.2 Relevant identified uses of the substance or mixture and uses

advised against No further relevant information available.

Application of the substance / the

mixture Wood treatment

Coating compound/ Surface coating/ paint

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier: Osmo Holz und Color GmbH & Co. KG

Affhüppen Esch 12 D-48231 Warendorf

Further information obtainable

from: Product safety department

Phone: +49 (0) 251 / 692 - 188 Fax: +49 (0) 251 / 692 - 462 e-mail: helmut.starp@osmo.de

1.4 Emergency telephone

number: emergency phone no. Berlin (24h): +49 (0) 30 / 30686 790 advisory service in German

and English

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to

Regulation (EC) No 1272/2008 The product is not classified, according to the CLP regulation.

2.2 Label elements

Labelling according to Regulation

(EC) No 1272/2008VoidHazard pictogramsVoidSignal wordVoidHazard statementsVoid

Precautionary statements If medical advice is needed, have product container or label at hand.

Keep out of reach of children.

P262 Do not get in eyes, on skin, or on clothing. P271 Use only outdoors or in a well-ventilated area.

Additional information: Observe the general safety regulations when handling chemicals.

Safety data sheet available on request.

Information concerning

particular hazards for human and

environment: Warning:

Wash out any used cloth impregnated with this product immediately after use or store

in an airtight container (danger of self-ignition)

(Contd. on page 2)



Printing date 22.05.2018 Version number 17 Revision: 13.03.2018

Trade name: Osmo Decking Oil

(Contd. of page 1)

30-60%

🚯 Asp. Tox. 1, H304

2.3 Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable.*vPvB*: Not applicable.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Description: Mixture of substances listed below with nonhazardous additions.

Dangerous components:

Additional information:

EC number: 918-481-9 aliphatic hydrocarbons, C10-C13

Index number: 649-327-00-6 Reg.nr.: 01-2119457273-39

For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information: Immediately remove any clothing soiled by the product.

Take affected persons out into the fresh air.

After inhalation: Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult

doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

After skin contact: Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.

After swallowing: If swallowed, seek medical advice immediately and show this container or label.

4.2 Most important symptoms and

effects, both acute and delayed Headache

Dizziness

4.3 Indication of any immediate medical attention and special

treatment needed No further relevant information available.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents: CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant

foam.

For safety reasons unsuitable

extinguishing agents: Water with full jet

(Contd. on page 3)



Printing date 22.05.2018 Version number 17 Revision: 13.03.2018

Trade name: Osmo Decking Oil

(Contd. of page 2)

5.2 Special hazards arising from

the substance or mixture Formation of toxic gases is possible during heating or in case of fire.

5.3 Advice for firefighters

Protective equipment: Mouth respiratory protective device.

Additional information Dispose of fire debris and contaminated fire fighting water in accordance with official

regulations.

Cool endangered receptacles with water spray.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and

emergency procedures Wear protective equipment. Keep unprotected persons away.

Keep away from ignition sources.

Ensure adequate ventilation

6.2 Environmental precautions: Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for

containment and cleaning up: Warm water and cleansing agent

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders).

6.4 Reference to other sections See Section 13 for disposal information.

No dangerous substances are released.

SECTION 7: Handling and storage

7.1 Precautions for safe handling Keep away from heat and direct sunlight.

Keep receptacles tightly sealed. Use only in well ventilated areas. Prevent formation of aerosols.

Information about fire - and

explosion protection: Keep ignition sources away - Do not smoke.

7.2 Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by

storerooms and receptacles: Store in a cool location.

Store only in the original receptacle.

Information about storage in one

common storage facility: Do not store together with alkalis (caustic solutions).

Do not store together with oxidising and acidic materials.

Further information about

storage conditions: Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

Storage class: 10

(Contd. on page 4)



Printing date 22.05.2018 Version number 17 Revision: 13.03.2018

Trade name: Osmo Decking Oil

(Contd. of page 3)

7.3 Specific end use(s)

No further relevant information available.

SECTION 8: Exposure controls/personal protection

Additional information about

design of technical facilities: No further data; see item 7.

8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

aliphatic hydrocarbons, C10-C13

TWA (8 H) Long-term value: 1,000 mg/m³, 150 ppm ppm

Source: UK SIA

Additional information: The lists valid during the making were used as basis.

8.2 Exposure controls

Personal protective equipment: General protective and hygienic

measures: Immediately remove all soiled and contaminated clothing

Keep away from foodstuffs, beverages and feed.

Avoid contact with the eyes and skin.

Do not eat, drink, smoke or sniff while working.

Do not carry product impregnated cleaning cloths in trouser pockets.

Respiratory protection: Use suitable respiratory protective device only when aerosol or mist is formed.

Not necessary if room is well-ventilated.

Protection of hands: To avoid skin problems reduce the wearing of gloves to the required minimum.

Selection of the glove material on consideration of the penetration times, rates of

diffusion and the degradation

The glove material has to be impermeable and resistant to the product/ the substance/

the preparation.

Material of gloves Nitrile rubber, NBR

Penetration time of glove material The exact break trough time has to be found out by the manufacturer of the protective

gloves and has to be observed.

For the permanent contact gloves made of the following materials

are suitable: Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.4 mm

As protection from splashes gloves made of the following

materials are suitable: Nitrile rubber, NBR

Eye protection: Goggles recommended during refilling

Body protection: Protective work clothing

(Contd. on page 5)



Printing date 22.05.2018 Version number 17 Revision: 13.03.2018

Trade name: Osmo Decking Oil

(Contd. of page 4)

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

General Information

Appearance:

Form: Fluid

Colour: According to product specification

Odour: Mild

Change in condition

Melting point/freezing point: Undetermined. *Initial boiling point and boiling range:* > 180 °C

Flash point: > 62 °C (DIN EN ISO 2719)

Ignition temperature: 240 °C

Auto-ignition temperature: Product is not selfigniting.

Explosive properties: Product is not explosive. However, formation of explosive air/vapour mixtures

are possible.

Explosion limits:

 Lower:
 0.6 Vol %

 Upper:
 7.0 Vol %

Density at 20 °C: 0.85 - 1.0 g/cm³ (DIN 51757)

Solubility in / Miscibility with

water: Not miscible or difficult to mix.

Viscosity:

Dynamic: Not determined.

Kinematic at 20 °C: 25-50 s (DIN 53211/3mm)

 $>21 \text{ mm}^2/\text{s} (40^{\circ}\text{C})$

9.2 Other information No further relevant information available.

SECTION 10: Stability and reactivity

10.1 Reactivity No further relevant information available.

10.2 Chemical stability
Thermal decomposition /

conditions to be avoided: No decomposition if used according to specifications.

10.3 Possibility of hazardous

reactions Reacts with fabric soaked in the product (e.g. cleaning wool).

10.4 Conditions to avoid No further relevant information available.10.5 Incompatible materials: No further relevant information available.

(Contd. on page 6)



Printing date 22.05.2018 Version number 17 Revision: 13.03.2018

Trade name: Osmo Decking Oil

(Contd. of page 5)

10.6 Hazardous decomposition

products: Carbon monoxide and carbon dioxide

Nitrogen oxides (NOx)

Additional information:

Warning:

Wash out any used cloth impregnated with this product immediately after use or store

in an airtight container (danger of self-ignition)

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:

aliphatic hydrocarbons, C10-C13

| Oral | LD50 | > 5000 mg/kg (rat) (OECD 401) |
|------------|-----------|-------------------------------|
| Dermal | LD50 | > 5000 mg/kg (rat) (OECD 402) |
| Inhalative | LC50 / 4h | 21 mg/l (rat) (OECD 403) |

Primary irritant effect:

Skin corrosion/irritation At long or repeated contact with skin it may cause dermatitis due to the degreesing

effect of the solvent.

Serious eye damage/irritation Based on available data, the classification criteria are not met. **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.

CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

Germ cell mutagenicityBased on available data, the classification criteria are not met.CarcinogenicityBased on available data, the classification criteria are not met.Reproductive toxicityBased on available data, the classification criteria are not met.STOT-single exposureBased on available data, the classification criteria are not met.STOT-repeated exposureBased on available data, the classification criteria are not met.Aspiration hazardBased on available data, the classification criteria are not met.

SECTION 12: Ecological information

12.1 Toxicity

| Aquatic toxicity: | | | |
|---------------------------------|----------------------------------|--|--|
| aliphatic hydrocarbons, C10-C13 | | | |
| EC50 / 48h | > 1000 mg/l (daphnia) (OECD 202) | | |
| EC50/72h | > 1000 mg/l (algae) (OECD 201) | | |
| LC50 / 96h | > 1000 mg/l (fish) (OECD 203) | | |
| Biolog. Abbaubarkeit | (leicht abbaubar) | | |

12.2 Persistence and degradability No further relevant information available.

12.3 Bioaccumulative potential No further relevant information available.

(Contd. on page 7)



Printing date 22.05.2018 Version number 17 Revision: 13.03.2018

Trade name: Osmo Decking Oil

(Contd. of page 6)

12.4 Mobility in soil No further relevant information available.

Additional ecological information:

General notes: Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for

water

12.5 Results of PBT and vPvB assessment

PBT: Not applicable.*vPvB*: Not applicable.

12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Recommendation Must not be disposed together with household garbage. Do not allow product to reach

sewage system.

| European waste catalogue | | | | |
|--------------------------|---|--|--|--|
| 08 01 11* | waste paint and varnish containing organic solvents or other dangerous substances | | | |
| 15 01 10* | packaging containing residues of or contaminated by dangerous substances | | | |

Uncleaned packaging:

Recommendation: Disposal must be made according to official regulations.

Recommended cleansing agents: Solvent naphtha

SECTION 14: Transport information

| 14.1 UN-Number ADR, ADN, IMDG, IATA | Void | |
|--|-----------------|--------------------|
| 14.2 UN proper shipping name ADR, ADN, IMDG, IATA | Void | |
| 14.3 Transport hazard class(es) | Void | |
| ADR, ADN, IMDG, IATA Class | Void | |
| 14.4 Packing group ADR, IMDG, IATA | Void | |
| 14.5 Environmental hazards: | | |
| Marine pollutant: | No | |
| 14.6 Special precautions for user | Not applicable. | |
| 14.7 Transport in bulk according to Annex II of Marpol | | |
| and the IBC Code | Not applicable. | |
| | | (Contd. on page 8) |

(Contd. on page 8)



Printing date 22.05.2018 Version number 17 Revision: 13.03.2018

| Trade name: Osmo Decking Oil | | | | |
|------------------------------|------|--------------------|--|--|
| | | (Contd. of page 7) | | |
| UN "Model Regulation": | Void | | | |

SECTION 15: Regulatory information

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Relevant phrases H304 May be fatal if swallowed and enters airways.

Department issuing SDS: product safety department

Contact: Hr. Dr. Starp

Abbreviations and acronyms: ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement

concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Asp. Tox. 1: Aspiration hazard – Category 1

GB