

Worktop Kit



Oiling of wooden worktops and furniture

WOCA Worktop Kit is used for oil treatment and maintenance of worktops and other indoor wood surfaces. The oil is easy to work with and creates a durable surface with high resistance. Worktop Oil is an air-hardening oil that penetrates deep into the wood, leaving a tough water- and stain-resistant surface. The oil highlights the wood's natural glow and gives the surface a natural, fresh appearance. Worktop Oil is safe for food contact and can be used on surfaces that are untreated or that have previously been oil-treated and sanded. The kit contains all you need for the entire treatment: 0.75 L Worktop Oil, 250 ml. Intensive Wood Cleaner, black sanding pad, white polishing pad, one lint-free cloth, one pair of gloves and work instructions.

- All you need – in one box
- Safe for food contact
- Contains natural oils
- Provides a dirt and water-resistant surface
- Long lasting natural appearance
- Can be used on all wood varieties

Application area

For the care and maintenance of untreated or previously oil-treated/sanded surfaces such as worktops, tabletops and kitchen furnitures. Only for indoor use.

Work description

Please note

Wood humidity must not exceed 18%. High temperature and low air humidity will reduce drying times. Low temperature and high air humidity will extend drying times. The worktop should be maintained at least once a year, or when necessary. For a superior result, use Worktop Oil or WOCA Maintenance Gel. For a more thorough restoration, follow the entire procedure.

Drying time

Between coats: 30-60 minutes at 20°C

Light use: 24 hours at 20°C

Recommendation: Until fully hardened the surface must be treated with care. All liquids must be removed immediately.

Fully hard: 7 days at 20°C

Technical data

Declaration: Less than 5%: non-ionic surfactants, cationic surfactants.

VOC: 10 g/l, maximum VOC content (A/i (SB)): 500 g/l.

Density: 0.90-0.95 g/ml.

Shelf life: 3 years

Application Temperature: +15-30°C and approx. 50% air humidity.

Coverage: 12-15 m²/L

Colours: Natural

Cleaning of tools: Use WOCA Solvent or turpentine

Storage: +10-25°C. Keep out of reach of children. Do not expose to heat (e.g. sunlight).
Store frost-free during winter and cool during summer.

Packaging: 1 L

Viscosity: 30-35 Sec. DIN Cup 4

Odour: Characteristic

Solid content: 70-75%

Maintenance and related products

Maintaining and cleaning

Cleaning: For daily cleaning, use WOCA Natural Soap or WOCA Natural Soap on spray.
Maintenance: Maintain the work surface with oil. For a superior result, use Worktop Oil or WOCA Maintenance Gel.

WOCA Denmark A/S
Tværvej 6
DK - 6640 Lunderskov
+45 9958 5600
info@wocadenmark.com
wocadenmark.com

This information is based on extensive laboratory testing and practical experience. Because the conditions under which the product is used are often beyond the control of WOCA Denmark, we can only guarantee the quality of the actual product. WOCA Denmark A/S accepts no liability for incorrect use and handling of the product. In principle, this product can be considered an intermediate product, as results depend on construction, the nature of the surface, pretreatment, temperature, air humidity, application etc. WOCA Denmark A/S reserves the right to change the product and the stated information without notice. This label/product description replaces all previous versions.